

EPS14TDE-UF



Europower super-silenced generating set with Kubota water-cooled diesel engine, 1500rpm, 50Hz, 4 stroke.

Generator

kVA max.	14
kVA cont.	13
Ampère (continu)	19A @ 1~230V 15A @ 3~400V
Dimensions (l x b x h)	144 x 115 x 78cm
Weight incl. oil + coolant, excl. fuel	550kg

Engine

Brand/Type	Kubota D1703M
HP	23.1
Power	12.8kW (1500rpm), 3-cylinder Diesel, Water-cooled
Displacement	1647cm ³
Consumption @75% load	2.6 litres/hour
Tank	170 litres
Autonomy @75% load	65 hours
Noise level	68dB(A) @7m = LwA 93
Electronic speed governor	standard
Battery voltage	12V

Alternator

Brand/Type	Sincro SK160CB - L3++ - brushless
Nominal voltage	3~400V and 1~230V
Frequency	50Hz
Protection degree	IP23

Versie

- 3 Ampere meters
- Automatic voltage regulator
- Fuel pump 12V
- Deep Sea Electronics module DSE4520 up to 275kVA and DSE7420 as of 300kVA
- Electric start, maintenance free battery included
- Electronic speed governor
- Frequency meter
- Insulation protection
- Magneto-stop
- Mechanical fuel level meter
- Low coolant level switch
- Low oil pressure guard
- High temperature security
- Thermal magnetic breaker
- Hour counter
- Voltmeter
- Water separator
- Oil drain hose
- Minimum level switch for radiator coolant
- Extra epoxy primer coating before polyester final coating
- Galvanised chassis
- Galvanised lifting frame
- Extra protection on the electric components
- Sincro SK160CB – alternator protection “L3++” for severe industrial environment



**DIGER
GENERATOREN**

☎ Tel : 00 32 3 542 00 00
 📠 Fax : 00 32 3 541 64 94
 📍 Address : Vosseschijnstraat 198
 B-2030 Antwerpen
 ✉ Email : info@diger.be